

# SAFETY DATA SHEET

## 1524 PRO FLEX CLEAR BLUE PART A

This Safety Data Sheet contains information concerning the potential risks to those involved in handling, transporting and working with the material, as well as describing potential risks to the consumer and the environment. This information must be made available to those who may come into contact with the material or are responsible for the use of the material. This Safety Data Sheet is prepared in accordance with formatting described in the REACH Regulation (EC) No 1907/2006, and described in CLP Regulation (EC) No 1272/2008.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier**  
1524 PRO FLEX CLEAR BLUE PART A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**  
Primer
- 1.3 Details of the supplier of the safety data sheet**  
Company Name: Pro Guard Coatings, Inc.  
Address One Industrial Way  
Address Denver, PA 17517 USA  
Address  
**Tel: 717-336-7900**  
Fax: 717-336-7320  
E mail:
- 1.4 Emergency telephone number**
- In case of emergency Tel. Chemtrec: 800-424-9300**

### SECTION 2: Hazards Identification

#### 2.1 Classification of the substance or mixture

##### Classification in accordance with the Dangerous Preparations Directive 1999/45/EC

Xi; R36/38  
R43  
Muta Cat 3; R68  
N; R51/53

##### Classification in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008

Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Skin Sens. 1 H317  
Muta Cat 2 H341  
Aquatic Chronic 2 H411

## 2.2 Label elements

Labelling in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008



### WARNING

- H315 Causes skin irritation  
 H319 Causes serious eye irritation  
 H317 May cause an allergic skin reaction  
 H341 Suspected of causing genetic defects  
 H411 Toxic to aquatic life with long lasting effects  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P273 Avoid release to the environment.  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P501 Dispose of contents/container to hazardous waste facility

### 2.3 Other hazards

No physical hazards are anticipated.

Expected to be irritant. Contains bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), oxirane, mono[(C12-14-alkyloxy)methyl] derivs and o-cresyl glycidyl ether which are considered to be sensitising and may cause an allergic reaction.

Contains components which are considered to be toxic to aquatic organisms. None of the components are considered to be Persistent, Bioaccumulative and Toxic (PBT) or very Persistent, very Bioaccumulative (vPvB).

## SECTION 3: Composition

### 3.1 Substances

Not applicable, product is a mixture.

### 3.2 Mixtures

A mixture of polymers, solvents and additives.

Name	CAS No.	Concentration % w/w	Classification
Bisphenol-A-(epichlorhydrin) epoxy resin (average molecular weight <= 700)	25068-38-6	>50%	Xi; R36/38, R43, N; R51/53 <i>DSD 67/548/EEC</i>
			Skin Irrit. 2 H315, Eye Irrit. 2 H319 Skin Sens. 1 H317, Aquatic Chronic 2 H411 <i>CLP 1272/2008</i>
o-Cresyl Glycidyl Ether	2210-79-9	10-20%	Xi; R38, R43, Muta Cat. 3 R68, N; R51/53 <i>DSD 67/548/EEC</i>
			Skin Irrit. 2 H315, Skin Sens. 1 H317 Muta. 2 H341, Aquatic Chronic 2 H411 <i>CLP 1272/2008</i>
Bisphenol A epoxy resin (molecular weight 700-1100)	67924-34-9	1-10	Xi; R36/38, R43 <i>DSD 67/548/EEC</i>

			Skin Irrit. 2 H315, Eye Irrit. 2 H319 Skin Sens. 1 H317 <i>CLP 1272/2008</i>
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	1-5%	Xi; R38, R43 <i>DSD 67/548/EEC</i> Skin Irrit. 2 H315, Skin Sens. 1 H317, <i>CLP 1272/2008</i>
Benzyl alcohol	100-51-6	1-5%	Xn; R20/22, Xi; R36 <i>DSD 67/548/EEC</i> Acute Tox. 4 H302, Acute Tox. 4 H332 Eye Irrit. 2 H319 <i>CLP 1272/2008</i>

See section 16 for full description of R phrases and H statements.

#### SECTION 4: First Aid Measures

##### 4.1 Description of first aid measures

**EYE CONTACT:** Rinse thoroughly with water for several minutes, whilst gently holding the eyelids open. Obtain medical attention if signs of discomfort.

**INHALATION:** Remove from exposure and keep warm and at rest. If breathing becomes difficult call a doctor. If breathing stops, begin artificial respiration and seek immediate medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Wash off with soap and water. Seek medical attention if irritation occurs. Wash contaminated clothing before re-use.

**INGESTION:** If swallowed, rinse mouth with water. Do NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

##### 4.2 Most important symptoms and effects, both acute and delayed

**EYES:** Redness, watering

**INHALATION:** Irritation of the mouth, nose and throat, coughing.

**INGESTION:** Irritation of the mouth and throat. Nausea, discomfort.

**SKIN:** Redness, irritation, rash. Chronic exposure may result in allergic skin reactions.

##### 4.3 Indication of any immediate medical attention and special treatments needed

Symptomatic treatment as required

#### SECTION 5: Firefighting Measures

##### 5.1 Extinguishing media

Small fires: Foam, CO<sub>2</sub>, dry chemical

Large fires: Water fog, foam, CO<sub>2</sub>, dry chemical

##### 5.2 Special hazards arising from the substance or mixture

Decomposition products will include oxides of carbon and nitrogen, incomplete combustion products.

##### 5.3 Advice for fire fighters

Prevent run-off from fire from entering water courses and sewers. Fire-fighters should use standard protective equipment and in enclosed spaces, positive pressure self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed containers..

#### SECTION 6: Accidental Release Measures

##### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all ignition sources and evacuate unnecessary personnel from the area. Ventilate the area if possible. Wear suitable protective clothing including solvent resistant gloves and coveralls. If vapour concentrations are high, respiratory protective equipment may be required. See section 8 for more information.

## 6.2 Environmental precautions

Prevent entry into sewers and watercourses. If product enters sewers or watercourses, inform the appropriate environmental authorities.

## 6.3 Methods and materials for containment and cleaning up

Small spills: Remove all ignition sources. Absorb spillage in a non-combustible absorbent, e.g. sand or vermiculite, and place in a suitable container for disposal.

Large spills: Remove all ignition sources. Contain spill and cover if possible to reduce evaporation. Mix spillage with a suitable non-combustible absorbent, e.g. sand or earth, and place in a suitable container for disposal.

## 6.4 References to other sections

See sections 8 and 13 for further advice on protective clothing and disposal.

## SECTION 7: Handling and Storage

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Use only in well ventilated areas. Avoid contact with all ignition sources, including hot surfaces.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well ventilated, bunded area, away from all ignition sources. Keep out of direct sunlight. Vapours are heavier than air and may accumulate in low lying areas and below ground areas such as ducts and sewers.

### 7.3 Specific end uses(s)

No industrial or sector specific guidance available.

## SECTION 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

No exposure limits available.

### 8.2 Exposure controls

#### Engineering controls

Adequate ventilation should be provided so that exposure limits are not exceeded. Use explosion-proof ventilation equipment.

#### Respiratory protection

Use only in well ventilated area. If exposure levels are likely to exceed the OEL then suitable respiratory protection will be required.

#### Hand Protection

Wear suitable chemical resistant gloves recommended for use with hydrocarbon solvent. Nitrile gloves may be suitable, but glove manufacturers' specifications should always be checked first. Natural rubber gloves are not suitable. Change gloves in accordance with manufacturer recommendations. If gloves are damaged during use, remove immediately and wash hands before replacing with new gloves.

#### Eye protection

Wear suitable eye protection, meeting the requirements of BS EN166 3, when handling this product.

#### Skin protection

Aprons or coveralls are recommended. These should be changed after use or if contaminated. Wash before re-use.

#### Environmental Exposure Controls

Take suitable measures to prevent entry into drains, sewers and watercourses.

## SECTION 9: Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	Clear viscous liquid
<b>Odour:</b>	Petroleum odour
<b>Odour threshold:</b>	No data available
<b>pH:</b>	Not applicable
<b>Melting point:</b>	No data available
<b>Boiling point:</b>	200-270°C
<b>Flashpoint:</b>	102°C
<b>Evaporation rate:</b>	Slower than ether
<b>Flammability (gas, solid):</b>	Not applicable
<b>Upper/lower flammability limits</b>	Not applicable
<b>Vapour pressure:</b>	No data available
<b>Vapour density:</b>	Heavier than air
<b>Relative density:</b>	1.2
<b>Solubility in water:</b>	Insoluble
<b>Solubility in other solvents:</b>	No data available
<b>Partition coefficient (log Kow):</b>	No data available
<b>Autoignition temperature:</b>	No data available
<b>Decomposition temperature:</b>	No data available
<b>Viscosity:</b>	No data available
<b>Explosive properties:</b>	Not classified as explosive
<b>Oxidising properties:</b>	Not classified as oxidising.

### 9.2 Other information

<b>VOC content:</b>	60 g/l
---------------------	--------

## SECTION 10: Stability and Reactivity

### 10.1 Reactivity

Not considered a reactive material.

### 10.2 Chemical stability

This material is stable under expected conditions of use.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Strong oxidisers.

### 10.6 Hazardous decomposition products

Material does not decompose under normal conditions of use. See section 5 for fire decomposition products.

## SECTION 11: Toxicological Information

### 11.1 Information on toxicological effects

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

- (a) **acute toxicity** Not expected to be acutely toxic, based on consideration of the components. Acute Toxicity Estimate (ATE) > 2000 mg/kg
- (b) **skin corrosion/irritation** Expected to be irritating to skin, based on consideration of the components.
- (c) **serious eye damage/irritation** Expected to be irritating to eyes, based on consideration of the components.
- (d) **respiratory/skin sensitisation** Expected to be sensitising, based on consideration of the components. Contains: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), bisphenol A epoxy resin (Molecular weight 700-1100, oxirane, mono[(C12-14-alkyloxy)methyl] derivs and o-Cresyl Glycidyl Ether
- (e) **germ cell mutagenicity** Contains o-Cresyl Glycidyl Ether which is classified as a suspected mutagen.
- (f) **carcinogenicity** Contains no components considered to be carcinogenic above thresholds of concern.
- (g) **reproductive toxicity** Contains no components considered to be hazardous to reproduction above thresholds of concern.
- (h) **STOT-single exposure** Not expected to cause organ damage. The solvents present may cause narcotic effects if inhaled or ingested in large quantities.
- (i) **STOT-repeated exposure** Not expected to cause organ damage from prolonged or repeated exposure.
- (j) **aspiration hazard** Not expected to be an aspiration hazard.

## SECTION 12: Ecological Information

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

### 12.1 Toxicity

This product contains components which are considered to be toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Once cured the toxicity of the product is expected to decrease.

### 12.2 Persistence and degradability

This product is not expected to be readily biodegradable.

### 12.3 Bioaccumulative potential

This product is expected to have a low bioaccumulation potential.

### 12.4 Mobility in soil

Cured product is expected to be immobile.

### 12.5 Results of PBT and vPvB assessment

None of the components are known to be PBT or vPvB.

### 12.6 Other adverse effects

None known.

## SECTION 13: Disposal Considerations

### 13.1 Waste treatment methods

Recover and recycle product if possible. If recovery and recycling are not possible, dispose of by incineration.

Empty containers may contain flammable residues. Do not puncture, cut or grind. Empty containers should be disposed of as hazardous waste.

Disposal should be in accordance with local and national regulations.

**SECTION 14: Transport Information**

	ADR	IMDG	ICAO
14.1 UN Number	NONE	NONE	NONE
14.2 UN Proper shipping name	NONE	NONE	NONE
14.3 Transport hazard class(es)	NONE	NONE	NONE
14.4 Packing group	NONE	NONE	NONE
14.5 Environmental hazards	NONE	NONE	NONE
14.6 Special precautions for user	NONE	NONE	NONE
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	NONE	NONE	NONE

**SECTION 15: Regulatory Information**
**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

All components are listed as existing substances in Europe

**15.2 Chemical Safety Assessment**

A Chemical Safety Assessment has not been carried out for this product.

**SECTION 16: Other Information**
**Revision information:**

This is a new SDS.

**List of Abbreviations used in this SDS:**

CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging Regulation (EC) no 1272/2008  
 DSD Dangerous Substances Directive 67/548/EEC  
 DPD Dangerous Preparations Directive 1999/45/EC  
 EC European Community/Commission  
 PBT Persistent, Bioaccumulative and Toxic  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) no 1907/2006  
 vPvB very Persistent, very Bioaccumulative

**References:**

ECHA CHEM database  
 Suppliers' SDSs for component substances

**Method used for classification of mixtures:**

Ingredient based approaches

**R Phrases and H Statements used in Section 3**

R10 Flammable  
 R36/38 Irritating to eyes and skin  
 R37 Irritating to respiratory system  
 R38 Irritating to skin

## 1524 PRO FLEX CLEAR BLUE PART A



Version number: 1.0  
Date: March 24, 2015  
Supercedes: not applicable

- R43 May cause sensitisation by skin contact
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- R65 Harmful: may cause lung damage if swallowed
- R66 Repeated exposure may cause skin dryness or cracking
- R68 Possible risk of irreversible effects

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H341 Suspected of causing genetic defects
- H411 Toxic to aquatic life with long lasting effects
- EUH066 Repeated exposure may cause skin dryness or cracking

### **Training requirements for workers**

No special requirements.