



Pro Guard 9120 Super Armor

Crystal Clear

Product Description

SUPER ARMOR CRYSTAL CLEAR was specifically formulated to waterproof and reduce dirt accumulation on glass and clear plastic: skylights, windows and domes

When applied to the exterior of a newly cleaned panel Super Armor Crystal Clear forms a nearly invisible coating which does not change the appearance of color or texture of the surface.

The highly hydrophobic nature of the coating makes it difficult for dirt to stick to it. Rain and occasional pressure washing will keep the surface clean. SUPER ARMOR CRYSTAL CLEAR also contains a permanent UV absorber to retard the rate of degradation from weathering.

Pro Guard Coatings has greatly improved the storage stability of SUPER ARMOR CRYSTALCLEAR by packaging the catalyst separately. When the catalyst is added, however, the mixed product must be applied in approximately one hour to prevent skinning or thickening in the container. The applied material will cure in 1 to 3 hours. Although SUPER ARMOR CRYSTAL CLEAR utilizes recently developed chemistry, it is based on a very durable Urethane Polymer which makes it reasonable to project a 10 year service life for the coating.

- Waterproofs porous surfaces
- Prevents dirt pickup
- Can be applied to damp surfaces
- Cures at low temperatures: 33 F (1C)
- Produces a clear invisible film, surface color is unchanged

Application

Add the pre-measured catalyst and apply by brush, roller or spray. Only mix enough coating that can be applied in ONE hour to prevent bodying in the container. Agitate material in container periodically to prevent skinning. Clean tools with Xylene, Toluene or Aromatic Naptha Solvents.

Product Data

Specific Gravity	1.06	Volatile Organic Compounds	32 gr/liter
Volume Solids	69.8%	Cure Time	3 - 5 hours
Spread Rate @ .25mm dry film (10 mil)	8.8 sq. m/gal 2.35 sq. m/liter		

The information presented herein is furnished free of charge and is based on technical data that Pro Guard believes to be reliable. It is intended for use by persons having technical skill and is at their own discretion and risk. Since conditions of use are outside our control we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate or a recommendation to infringe any patents.



One Industrial Way Denver, PA 17517

P (717) 336-7900 | F (717) 336-7320 | Toll Free (1-800) 735-4399

Web site www.proguardcoatings.com | E-mail info@proguardcoatings.com